

FIBERGLASS DOSING GFD

Small-weigh-feeder in completely closed design
for pre-chopped fiberglass

TECHNICAL DATA:

Conveying material:	pre-chopped fiberglass
Conveying capacity:	5 kg/h up to 3000 kg/h
Belt speed:	depending on the set point and the belt load
Belt width:	300 mm up to 800 mm
Bulk density:	300 kg/m³ up to 1500 kg/m³
Fibre length:	5 mm up to 21 mm
Inclination:	horizontal up to 8 degrees increasing or decreasing
Adjustment range:	1:10 (upgradeable up to 1:50 with feedback-encoder)
ATEX:	versions available
Accuracy:	± 1,0 %

If required customized special solutions are available!

REQUIREMENTS:

stable vibration-free subconstruction

SIGNIFICANT BENEFITS:

- | test weight for an easy and quick check of the weighing accuracy
- | integrated belt steering and tensioning device
- | completely closed system
- | minimal maintenance works
- | material-friendly

Gypsum
Construction material
Cement | Chemistry
Plastics
...



FUNCTION OF THE FIBERGLASS DOSING SYSTEM, GFD

KUKLA has developed specifically a weighing- and dosing system for pre-chopped fiberglass. This weigh feeder is particularly used for the production of gypsum plasterboards and wherever pre-chopped fiberglass is used. By means of several weighing systems, a special back combing as well as a special combing brush the pre-chopped fiberglass is accurately fed to the process. An upstream discharge device (ASG) is used for pre-dosing the fiberglass, which can be directly discharged from a Big-Bag. All weighing, dosing and control functions are performed by one KUKLA-weighing electronics. Each standard scale of KUKLA is equipped with a test weight device which makes possible a quick and easy check of weighing accuracy within a few minutes. An integrated, weight-loaded belt steering- and tensioning device guarantees a high accuracy and high reliability.

Price on request: office@kukla.co.at or 0043 / (0)7672 / 26666 - 0

Entrusted as a trade secret. All rights reserved.

KUKLA WAAGENFABRIK GMBH & CO KG

Stefan-Fadinger-Str. 1 – 11 | 4840 Vöcklabruck | AUSTRIA | Phone: +43 (0) 7672 266 66-0 | Fax: +43 (0) 7672 266 66-39 | Mail: office@kukla.co.at | www.kukla.co.at